





\$680RFID Time & Attendance Terminal

S680 is an RFID Time & Attendance and Access Control Terminal with 3.5" TFT LCD. With the adoption of the brand new firmware and the latest core board platform, S680 perfected its user-friendly

interface and identification speed, it can also control the door and connect with 3rd party electric lock, door sensor, and exit button, etc.

Features

Remarkable User Experience

- Intuitive and stunning UI designed with the most popular and
- internationalized element.
- Interface operation adopts modularized hierarchical design.
- Simpler, better and more logical.
- Great user interactivity.

Enhanced Features and Performance

- Multi-languages.
- Data backup and retrieve.
- Chip encryption for firmware protection.


Excellent Expandability

• Easy to extend functions and customize customers' requirements.

Specifications

| ID Card Capacity | 10,000 |
|--------------------------|---|
| Record Capacity | 50,000 |
| Display | 3.5-inch TFT Screen |
| Communication | TCP/IP, RS232/485, USB (host and client) |
| Standard Functions | Workcode, SMS, DST, Self-Service Query, AutomaticStatus Switch, Scheduled-bell, Photo ID, Anti-passback, ID Card |
| Access Control Interface | 3rd Party Electric Lock, Door Sensor, Exit Button, Alarm |
| Optional Functions | Mifare/HID, GPRS, Wi-Fi, 3G, Webserver, ADMS, Multiple Verify Mode, External Printer |
| Wiegand Sigal | Input & Output |
| Software | ZKTime Enterprise, ZKTime Small Business, BioTime 7, ZKTime.Net 3.0 |
| Power Supply | DC 12V 1.5A |
| Verification Speed | ≤1 Sec. |
| Operating Temp. | 0°C- 45°C |
| Operating Humidity | 20% - 80% |
| Dimension | 204.99×145.00×47.45mm (Length×Width×Thickness) |

Configuration



What's in the Box

